


Technical Data Sheet	<h1 style="color: red; margin: 0;">Rosenberger</h1>
-----------------------------	---

Cable assembly RPC-1.00 Plug – RTK 055 – RPC-1.00 Jack	<h2 style="margin: 0;">L70-287-XXX</h2>
--	---



All dimensions are in mm; tolerances: ± 3mm for A ≤ 300 mm; ± 1% for A > 300 mm
 *) If length "A" ≤ 90 mm marking is mount centric ± 5mm

Available variants

Type	max. Insertion loss	Marking	Weight (g) / pce
L70-287-XXX	$\leq 0.0018 * \sqrt{f[\text{GHz}]} + 0.00008 * f[\text{GHz}] \frac{\text{dB}}{\text{mm}}$	ROSENBERGER L70-287-XXX YYYY-WW SSSS	$0.0049 \frac{\text{g}}{\text{mm}} * A[\text{mm}] + 6.2\text{g}$

XXX – length in mm = A Maximum possible length = 6000mm
 WW – week YYYY – year ssss – serial no.

Note: Weight:
 First constant = Cable weight per mm; Second Constant = Connector left and Connector right weight per pce

Assembly parts

Connector left	RPC-1.00 plug
Connector right	RPC-1.00 jack
Cable	RTK 055
Armour	none

Electrical data

Impedance	50 Ω
Frequency	DC to 110 GHz
Return loss ¹	≥ 17 dB, DC to 50 GHz ≥ 14 dB, 50 to 110 GHz
Insertion loss ¹	see table available variants

Individual testing and documentation:
 Measurement plot with all 4 S – Parameters (S11; S22; S21; S12) is included with the cable assembly and on the backside the care and handling instruction is printed.

¹ Return Loss and Insertion Loss includes the measurement adaptor

Mechanical data

Minimum bend radius static	3.2 mm
Minimum bend radius dynamic	25.4 mm

Environmental data

Temperature range	- 40 °C to +125 °C
RoHS	compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Martin Moder	10.06.15	Markus Müller	08.04.19	b00	19-0462	Marion Striegler	08.04.19

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de	Tel. : +49 8684 18-0 Email : info@rosenberger.de	Page 1 / 1
--	---	---------------